

# 79 G SERIES SPECIFICATIONS



## General

Description	Monochrome wide format print/copy/scan with colour scanner
Type	Electrophotography (LED) with organic photoconductor (OPC) and closed toner system
Range of Productivity	14 D / A1 per minute / 840 prints per hour
Warm Up Time (from cold)	Less than 2 minutes from standby
Configuration	Printer / MFP
Roll Options	4 Roll
Output Delivery	Top / Optional Rear
Dimensions	67" (w) x 33" (d) x 59" (h) / 1702 mm x 835 mm x 1500 mm
Weight	MFP (4 Roll) 915 lb. / 415 kg   Printer (4 Roll) 860 lb. / 390 kg
Electrical Requirements	220V-240V +6% or -10%, 50/60Hz, 13A
Power Consumption (Standby)	1,100W
Power Consumption (Printing)	<2,650W
Power Consumption (Sleep)	<7W

## Printer

Print Resolution	600 dpi x 2400 dpi
Roll Capacity	4 Roll
Output Sizes Width	11" - 36"
Output Sizes Length	20' / 6 m (standard), 500'/150 m based on media validation
Media Types	Bond 18-24 lb. (80-110g), Vellum/Translucent Bond 18-20 lb. (80-90g), Film 3.5 - 4 mil (90-100 micron)

## Controller

Controller Type	KIP System K Controller with Microsoft® IoT Enterprise
Memory	2GB DDR3 Standard - Upgradeable to 4 GB
SSD	Minimum 320 GB - Unlimited Upgrade
Supported File Type	DWF, PDF, PDF-A, HPGL 1/2, HP-RTL, Calcomp 906/907, CALS Group 4, TIFF Group 4, CIT/TG4, Grayscale TIFF, TIFF Packbits, PNG, JPEG

## Scanner

Scanner Type	CIS / CCD
Scan Resolution	600 dpi
Scan Format	TIFF, Multipage TIFF, PDF, PDF-A, Multipage PDF, DWF, JPEG
Scan Destination	Lokaler USB (Wechselmedien), Mailboxen (lokal), SMB, FTP, Cloud, Email
Original Size Width	11" - 36" / 210 mm to 914 mm
Original Thickness	0.05 mm - 1.60 mm (image quality over 0.25 mm not guaranteed)



Scan to watch videos & get more KIP 79 G Series info  
or visit: [www.KIP.com/79](http://www.KIP.com/79)



KIP is a registered trademark of the KIP Group. All other product names mentioned herein are trademarks of their respective companies.  
All product features and specifications are subject to change without notice. Complete product specifications are available at [www.kip.com](http://www.kip.com). © 2023


V10/20/23-EU

# 79 G SERIES INSTALLATION



Space, Electrical, and Environmental Requirements	
Weight	MFP (4 Roll) 915 lb. / 415 kg   Printer (4 Roll) 860 lb. / 390 kg
Dimensions	67" (w) x 33" (d) x 59" (h) / 1702 mm x 835 mm x 1500 mm
Electrical (Dedicated)	220V-240V +6% or -10%, 50/60Hz, 15A
Electrical Receptacle	Nema 6-20 R
Max. Power Consumption	2,650 W (printing), 1,100 W (standby), 6 W (sleep)
Acoustic Noise	Idle: max. 50 db   Printing: max. 57 db
Room Temperature	50-86°F (10-32°C)
Room Humidity	15-85% (non condensing)

## Spatial Requirements (top view not to scale)



\* L + R = 14" / 350 mm or larger  
(R must be larger than L)  
(L = 2" / 50 mm or larger)

